



## AGRIMAX FORCE

### Description

AGRIMAX FORCE the high-end product of BKT is a radial tire specially designed for soil tillage, haulage and harvesting applications with high-power tractors and harvesters, ensuring top performance and efficiency. Thanks to its IF technology, this tire can carry heavy loads with a lower inflating pressure compared to a standard tire reducing soil compaction. AGRIMAX FORCE features a reinforced bead and provides enhanced traction, top self-cleaning properties and fuel economy.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Harvester



Version	STANDARD
Tire Type	TL
Tyre size	if650/75R38
LI/SS	175;D

## Dimensions IS Standard

SW (mm)	651
OD (mm)	1941
SLR (mm)	866
RC (mm)	5802
Rim Rec	DW 23 B
Rim Alt	DW 21 B
ECE	E11-106R-007385
TRA Code	R1W

## Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>70</b>	2955	3395	3895	4400	4900	5405	5905	6280
<b>From 65 to 40</b>	3245	3730	4280	4830	5385	5935	6490	6900
<b>30</b>	3375	3880	4455	5030	5605	6175	6750	7180
<b>20</b>	3505	4030	4625	5220	5815	6415	7010	7455
<b>10</b>	4120	4735	5435	6140	6840	7540	8240	8765
<b>Upto 30 Cyc</b>	4220	4845	5565	6280	7000	7715	8435	8970
<b>Upto 15 Cyc</b>	5030	5780	6635	7490	8345	9200	10055	10695
<b>Upto 10 Cyc</b>	5515	6335	7275	8215	9150	10090	11030	11730
<b>10 HT</b>	3375	3880	4455	5030	5605	6175	6750	7180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..