



IS standard



GROWING TOGETHER

AGRIMAX FACTOR



PRODUCT DATA SHEET

AGRIMAXFACTOR



AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent. In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of e-vehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.



Radial

R-1W



D



Technologies



E-Ready



High Speed



Heavy Duty

Performance



Durability



Stability



Steering Control



Handling and Comfort

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 24"	360/70 R 24	122 D/ 125 A8	W 11	W 10 ; W 12	357	1140	522	3386	550	STD
	NEWSIZE									
	380/70 R 24	125 D/ 128 A8	W 12	W 11 ; W 13	380	1190	538	3524	575	STD
	420/70 R 24	130 D/ 133 A8	W 13	W 12 ; W 14 L	418	1248	550	3649	600	STD
	420/70 R 24	134 D/ 137 A8	W 13	W 12 ; W 14 L	418	1248	563	3696	600	STD
Ø 28"	480/70 R 24	138 D/ 141 A8	W 15 L	W 14 L ; W 16 L	485	1311	590	3895	625	STD
	NEWSIZE									
	360/70 R 28	125 D/ 128 A8	W 11	W 10 ; W 12	357	1255	577	3747	600	STD
Ø 30"	NEWSIZE									
	380/70 R 28	127 D/ 130 A8	W 12	W 11 ; W 13	380	1293	588	3836	625	STD
	420/70 R 28	133 D/ 136 A8	W 13	W 12 ; W 14 L	418	1349	606	4000	650	STD
	480/70 R 28	140 D/ 143 A8	W 15 L	W 14 L ; W 16 L	479	1421	639	4239	675	STD
	600/70 R 28	157 D/ 160 A8	DW 20 B	DW 18 L ; W 18 L	611	1551	714	4667	725	STD
Ø 34"	420/70 R 30	134 D/ 137 A8	W 13	W 12 ; W 14 L	428	1391	633	4152	675	STD
	NEWSIZE									
	480/70 R 30	141 D/ 144 A8	W 15 L	W 14 L ; W 16 L	479	1478	670	4391	700	STD
Ø 34"	600/70 R 30	152 D/ 155 A8	DW 20 B	DW 18 L ; W 18 L	611	1602	722	4765	750	STD
	480/70 R 34	149 D/ 152 A8	W 15 L	W 14 L ; W 16 L	479	1580	723	4748	750	STD
Ø 34"	480/70 R 34	155 D/ 158 A8	W 15 L	W 14 L ; W 16 L	479	1580	729	4761	750	STD

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index





Radial



Technologies



Performance



	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 38"	480/70 R 38	145 D/ 148 A8	W 15 L	W 14 L ; W 16 L	479	1681	758	5000	800	STD
	520/70 R 38	150 D/ 153 A8	W 16 L	W 15 L ; W 18 L	516	1749	795	5239	825	STD
	580/70 R 38	155 D/ 158 A8	W 18 L	DW 18 L ; DD 18 L	577	1827	823	5456	875	STD
	620/70 R 38	170 D/ 173 A8	DW 20 B	DW 18 L ; W 18 L	625	1833	844	5580	875	STD
	710/70 R 38	166 D/ 169 A8	DW 23 B	-	716	1959	866	5800	925	STD
	710/70 R 38	171 D/ 174 A8	DW 23 B	DW 25 B	716	1959	866	5800	925	STD
	710/70 R 38	175 D/ 178 A8	DW 23 B	-	716	1959	866	5800	925	STD
Ø 42"	580/70 R 42	158 D/ 161 A8	W 18 L	DW 18 L ; DD 18 L	577	1879	856	5693	900	STD
	620/70 R 42	160 D/ 163 A8	DW 20 B	DW 18 L ; W 18 L	625	1935	863	5786	925	STD
	620/70 R 42	166 D/ 169 A8	DW 20 B	DW 18 L ; W 18 L	625	1935	876	5801	925	STD
	620/70 R 42	173 D/ 176 A8	DW 20 B	DW 18 L ; W 18 L	625	1935	876	5804	925	STD
	710/70 R 42	173 D/ 176 A8	DW 23 B	DW 25 B	716	2061	935	6198	975	STD
	710/70 R 42	176 D/ 179 A8	DW 23 B	DW 25 B	716	2061	935	6198	975	STD
Ø 46"	620/70 R 46	162 D/ 165 A8	DW 20 B	-	625	2036	913	6075	975	STD

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index

