



MULTIMAX MP 522



Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ▪ Compact Loader, Industrial & Construction ▪ Compact Loader

Version	STANDARD
Tire Type	TL
Tyre size	540/70R24
LI/SS	168;A8/B

Dimensions US Standard

USA Code	94052264
SW (US) (in)	20.9
OD (US) (in)	53.8
SLR (US) (in)	24.1
RC (US) (in)	162.7
Rim Rec	DW 16 L
Rim Alt	DW 18 L
ECE	E11-106R-002967

Load Capacity (US)

mph / psi	23	29	35	41	46	51	58	61	64
30	5930	7040	8020	9140	10250	10990	12350	-	-
25	5930	7040	8020	9140	10250	10990	12350	-	-
20	6350	7540	8600	9790	10980	11770	13220	-	-
15	6590	7830	8920	10150	11390	12210	13710	-	-
5 Cyc.	7230	8900	10470	12040	13710	14910	16850	17780	18520
Static	11080	13630	16050	18460	21020	22860	25850	27260	28390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..