



US standard



GROWING TOGETHER

AGRIMAX

RADIAL TRACTOR TIRES

TURF RT 333



PRODUCT DATA SHEET



Radial

R-1W

B

149



AGRIMAX TURF RT 333

RADIAL TRACTOR TIRES

🇺🇸 AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

Technologies



Extra Deep Tread



Block Pattern

Performance



Durability



Reduced Soil Compaction



Traction



Self-Cleaning



Low Rolling Resistance

| | US CODE | Tire size | LI/SS | RIM | | S.W. (In.) | O.D. (In.) | SLR (In.) | RC (In.) | TREAD DEPTH (32nds) | TIRE WEIGHT (lbs) | Version |
|----------|-------------|------------------|------------------|--------------|---------------|---------------|---------------|--------------|-------------|------------------------|----------------------|---------|
| | | | | Rec. | Alt. | | | | | | | |
| Ø 12" | 94070237 | 220/55 R 12 | 82 A8/B | 7 | - | 8.7 | 21.7 | 9.8 | 64.8 | 18 | 24 | STD |
| | 94070657 | 240/60 R 12 | 89 A8/B | 7 | - | 9.5 | 23.3 | 10.6 | 70.0 | 18 | 31 | STD |
| Ø 14" | 94076277 | 215/65 R 14 | 90 A8/ 90 B | W 7 | W 6 | 8.7 | 24.8 | 11.4 | 75.0 | 22 | 33 | STD |
| Ø 16" | 94070640 | 200/65 R 16 | 94 A8/B | W 6 | - | 8.0 | 26.2 | 12.2 | 78.7 | 25 | 35 | STD |
| | 94074136 | 200/70 R 16 | 94 A8/B | W 6 | - | 7.9 | 27.0 | 12.5 | 80.9 | 25 | 35 | STD |
| | 94070282 | 240/70 R 16 | 104 A8/B | W 8 | W 8 L; W 9 | 9.6 | 29.2 | 13.4 | 87.1 | 28 | 48 | STD |
| | 94067909 | 260/70 R 16 | 109 A8/ 109 B | W 8 | W 8 L; W 9 | 10.2 | 30.3 | 13.7 | 90.0 | 28 | 52 | STD |
| 94065714 | 280/70 R 16 | 112 A8/ 112 B | W 9 | W 8; W 10 | 11.4 | 31.5 | 14.1 | 93.3 | 30 | 59 | STD | |
| Ø 18" | 94065707 | 280/70 R 18 | 114 A8/ 114 B | W 9 | W 8; W 10 | 11.4 | 33.1 | 15.4 | 100.4 | 30 | 65 | STD |
| | 94071081 | 320/65 R 18 | 109 A8/ 109 B | W 10 | W 9; W 11 | 12.6 | 34.4 | 15.5 | 102.0 | 31 | 77 | STD |
| Ø 20" | 9406748 | 300/70 R 20 | 110 A8/ 110 B | W 9 | W 10 | 11.6 | 37.5 | 17.0 | 111.3 | 31 | 82 | STD |
| | 94067558 | 320/70 R 20 | 113 A8/ 113 B | W 10 | W 9; W 11 | 12.6 | 38.7 | 17.4 | 114.8 | 32 | 92 | STD |
| | 94068821 | 380/70 R 20 | 122 A8/ 122 B | W 12 | W 11; W 13 | 15.0 | 42.6 | 19.1 | 126.5 | 33 | 133 | STD |

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial



Technologies



Extra Deep Tread



Block Pattern

Performance



Durability



Reduced Soil Compaction



Traction



Self-Cleaning



Low Rolling Resistance



| | US CODE | Tire size | LI/SS | RIM | | S.W. (In.) | O.D. (In.) | SLR (In.) | RC (In.) | TREAD DEPTH (32nds) | TIRE WEIGHT (lbs) | Version |
|-------|----------|-------------|------------------|--------|----------------------------|---------------|---------------|--------------|-------------|---------------------------|-------------------------|---------|
| | | | | Rec. | Alt. | | | | | | | |
| Ø 24" | 94067916 | 360/70 R 24 | 122 A8/ 122 B | W 11 | W 10 ; W 12 | 14.1 | 45.4 | 20.4 | 134.2 | 32 | 134 | STD |
| | 94068838 | 380/70 R 24 | 125 A8/ 125 B | W 12 | W 11 ; W 13 | 15.0 | 46.9 | 21.0 | 139.3 | 33 | 150 | STD |
| | 94069460 | 420/70 R 24 | 130 A8/ 130 B | W 13 | W 12 ; W 14 L | 16.5 | 49.1 | 21.9 | 146.8 | 35 | 181 | STD |
| | 94501649 | 420/85 R 24 | 137 A8/ 137 B | W 15 L | DW 15 L ; DW 14 L | 17.1 | 52.1 | 23.4 | 155.8 | 36 | 196 | STD |
| Ø 28" | 94076390 | 340/85 R 28 | 127 A8/ 127 B | W 12 | W 11 ; DW 11 ; DW 12 | 14.6 | 50.7 | 23.0 | 152.5 | 32 | 147 | STD |
| | 94075393 | 480/70 R 28 | 140 A8/ 140 B | W 15 L | W 14 L ; W 16 L | 18.9 | 55.9 | 24.8 | 166.5 | 36 | 242 | STD |
| Ø 30" | 94075409 | 480/70 R 30 | 141 A8/ 141 B | W 15 L | W 14 L ; W 16 L | 18.9 | 58.2 | 26.0 | 173.1 | 38 | 254 | STD |
| Ø 34" | 94075232 | 480/70 R 34 | 149 A8/ 149 B | W 15 L | W 14 L ; W 16 L | 19.3 | 62.2 | 28.5 | 188.4 | 38 | 278 | STD |

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference