



US standard



GROWING TOGETHER

MULTIMAX
RADIAL MPT TIRES
MP 515



PRODUCT DATA SHEET



Radial



MULTIMAX MP 515

RADIAL MPT TIRES

MULTIMAX MP 515 is an agro-industrial radial tire designed for universal vehicles and fertilizer trucks. It is suitable for municipality and transport applications. The tire shows a unique tread design providing superior riding comfort on the road as well as excellent self-cleaning properties and great traction. The strong steel-belted nylon casing and the reinforced shoulder ensure extraordinary durability. MULTIMAX MP 515 is the perfect tire also at high speeds (90km/h).

Technologies



High Speed



Reinforced Shoulder



Steel Belted

Performance



Durability



Handling and Comfort



Self-Cleaning



Traction

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 20"	94056545	405/70 R 20 MPT	136 G	13	13 SDC ; 12 SDC ; 11 SDC ; 11	16	42.4	19.4	129.4	35	154	STD
	94055975	425/75 R 20 MPT	148 G	13	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12	16.6	45.1	20.6	137.4	39	182	STD
Ø 22.5"	94057207	445/65 R 22.5 MPT	160 G	13	14	17.5	45.3	20.7	139.1	40	193	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference