



US standard



GROWING TOGETHER

# TR 317



PRODUCT DATA SHEET



Bias



# TR 317

TR 317 is suitable for municipality and soil tillage operations with implement machinery, trenchers and orchard harvesters. The TR 317 tire has a large contact area which provides excellent grip and outstanding stability in any condition along with great self-cleaning properties.

### Performance



Self-Cleaning



Stability



Traction

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
$\varnothing$ 8"	94045884	18 X 8.50 - 8	7.00 I - 55 ; I - 70 ; I - 90	-	8.5	17.7	7.8	51.4	18	13	HD	6	TL	-
	94038879	18 X 8.50 - 8	7.00 I - 55 ; I - 70 ; I - 90	-	8.5	17.7	7.8	51.4	18	12	STD	4	TL	-

HD: Heavy Duty - STD: Standard



Tolerances: O.D.  $\pm$  2% - S.W.  $\pm$  2% - RC  $\pm$  2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference