



US standard



GROWING TOGETHER

# MAGLIFT LOADER



PRODUCT DATA SHEET



Solid



# MAGLIFT LOADER

MAGLIFT LOADER has been specially designed for wheel loaders operating in the most demanding applications such as demolition works, scrap metal recycling, waste transfer and mining. Indeed, the particular tread design provides excellent traction under heavy-duty service conditions, whilst the reinforced bead structure ensures best grip and eliminates any slippage risk during operations. MAGLIFT LOADER is made of an extraordinarily cut-and-chip-resistant tread compound and has a two-layer solid construction. This avoids the risk of punctures or other damage ensuring higher productivity along with an extended tire life-cycle. In addition, the sidewall geometry with specifically developed apertures provides a cushioning effect that absorbs and dampens vibrations and impacts, thus improving operator's comfort and preventing back pain. The cushioning effect also helps to reduce equipment maintenance.

**Technologies**



Heavy Duty



Reinforced Bead

**Performance**



Traction



Cut and Chip Resistance



Durability



High Puncture Resistance



Comfort

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	O.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 25"	94074761	20.5 - 25 (525/80 - 25)	-	-	-	STD	58.9	20.5	-	-	265	1574	17.00/2.0	-

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference