



US standard



GROWING TOGETHER

# MULTIMAX

RADIAL MPT TIRES

## MP 569



PRODUCT DATA SHEET

**MULTIMAX MP 569**  
RADIAL MPT TIRES

🇺🇸 MULTIMAX MP 569 is a high-performance radial tire engineered for demanding industrial applications. MULTIMAX MP 569 is the ideal choice for equipping telehandlers and other construction equipment such as industrial tractors and excavators. The deep tread design, combined with wide shoulder lugs, ensures exceptional traction and flotation on multiple surfaces. The tire's All-Steel radial construction provides exceptional durability and superior resistance to punctures, significantly extending service life. Designed with angled directional lugs, the tread design facilitates effective self-cleaning, while the central tread blocks help maintain continuous ground contact, contributing to smooth roadability. This integrated tread design, featuring both center blocks and shoulder lugs, makes MULTIMAX MP 569 highly versatile and suitable for both on- and off-the-road applications.



Radial



180

**Technologies**



All Steel



High Speed

**Performance**



Traction



Self-Cleaning



Comfort



Low Rolling Resistance



Durability



Stability

	US CODE	Tire size	LI/SS	RIM		O.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 19.5"	94514380	445/70 R 19.5 (18 R 19.5)	173 A8/ 180 A2	14.00	-	17.8	43.8	19.6	132.4	30	244	STD
		<b>NEWSIZE</b>										
Ø 22.5"	94067268	445/65 R 22.5 (18 R 22.5)	169 J	13.00	14.00	17.3	46.2	20.8	140.1	35	278	STD

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference