



IS standard



GROWING TOGETHER

# MAGLIFT SMOOTH



PRODUCT DATA SHEET



Solid



# MAGLIFT SMOOTH

MAGLIFT SMOOTH has been particularly designed for ground support equipment (GSE), port and industrial trailers operating on smooth surfaces. The tire is made of a special tread compound, which ensures excellent cut and chip resistance and a long tire life. The smooth tread design and its maximum contact area provide extraordinary stability and optimized load distribution even under heavy-duty service conditions. MAGLIFT SMOOTH stands for excellent traction as well as low rolling resistance and low heat built up for improved efficiency. In addition, the specifically designed rim guard ensures protection against wheel damage, whilst the reinforced bead structure ensures best grip and eliminates any slippage risk during operations.

## Technologies



Special Compound



Smooth Tire



Reinforced Bead

## Performance



Cut and Chip Resistance



Stability



Traction



Low Rolling Resistance



Durability

	Tire size	Type	PR	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 15"	300 - 15	-	-	-	STD	255	820	-	-	8.00 - 15	-
Ø 20"	10.00 - 20	-	-	-	STD	254	1015	-	-	7.50 - 20	-
	10.00 - 20	-	-	-	STD	266	1015	-	-	8.00 - 20	-
	11.00 - 20	-	-	-	STD	256	1055	-	-	8.00 - 20	-
	11.00 - 20	-	-	-	STD	256	1055	-	-	7.50 - 20	-
	12.00 - 20	-	-	-	STD	282	1088	-	-	8.50 - 20	-
	12.00 - 20	-	-	-	STD	269	1088	-	-	8.00 - 20	-

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference