



IS standard



GROWING TOGETHER

FL 639



PRODUCT DATA SHEET



Radial



FL 639

FL 639 is a field-oriented flotation radial tire also suitable for spreading applications. Its wide footprint area ensures low soil compaction resulting in increased crop productivity. The reinforced bead and the sidewall protection contribute to an extended tire life-cycle. FL 639 ensures extraordinary traction along with great self-cleaning properties.

Technologies



Reinforced Bead



High Speed

Performance



Reduced Soil Compaction



Traction



Self-Cleaning



Durability

	Tire size	LI/SS		RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
		DW	FR	Rec.	Alt.						
Ø 22.5"	560/45 R 22.5	152 D/163 A8		AG 16.00	-	543	1076	484	3303	525	STD
	600/50 R 22.5	159 D/170 A8		AG 20.00	-	611	1172	530	3540	550	STD
	600/50 R 22.5	156 B	168 B	AG 20.00	-	611	1172	521	3592	550	STD
	710/40 R 22.5	161 D/172 A8		AG 24.00	-	727	1140	503	3492	550	STD
	710/40 R 22.5	158 B	170 B	AG 24.00	-	727	1140	503	3492	550	STD
	800/40 R 22.5	168 D/178 A8		AG 28.00	-	828	1212	538	3642	575	STD
NEWSIZE											
Ø 26.5"	850/40 R 26.5	173 D/184 A8		AG 28.00	-	860	1355	599	4122	650	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index; DW = Drive Wheel; FR = Free Rolling