



US standard



GROWING TOGETHER

F 240



PRODUCT DATA SHEET



Bias



Performance



Cut Resistance



Durability



Self-Cleaning



Traction



F 240

F 240 is a forestry tire designed for logging applications. Its tread pattern provides excellent traction, self-cleaning properties in addition to good steering. The superior tread compound ensures extraordinary cut-and-wear resistance resulting in a longer service life. F 240 shows a large contact area for better stability.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
\varnothing 15.5"	94052004	18 - 15.5	AG 13.00	-	17.7	39.0	16.9	115.4	17	128	STD	14	TT	-
	94051588	400 - 15.5 (400 - 15.5)	AG 13.00	-	15.9	34.1	-	-	17	93	STD	12	TT	-

STD: Standard



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference