



US standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 55



PRODUCT DATA SHEET



Radial

L-5S

A2

229



EARTHMAX SR 55

RADIAL OTR TIRES

EARTHMAX SR 55 is an All Steel Radial tire specially designed for loaders and load haul dumps operating in the most severe underground mining operations, and at scrapyards. Thanks to excellent cut protection resulting from the extra-deep and smooth tread design, EARTHMAX SR 55 is able to achieve peak productivity with reduced downtime along with excellent durability. Equipment operators will also appreciate extraordinary stability.

Technologies



Smooth Tire



Extra Deep Tread

Performance



Stability



Durability



Cut Resistance

	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	TRA CODE	TMPH	O.D. (In.)	O.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
															Rec.	Alt.
Ø 24"	94071463	12.00 R 24	TT	**	175 A2	CRC	L-5S	-	50.2	12.0	22.5	149.1	73	407	8.50/1.3	8.0 ; 9.0
	94071470	12.00 R 24	TL	**	175 A2	CRC	L-5S	-	50.2	12.0	22.5	149.1	73	407	8.50/1.3	8.0 ; 9.0
Ø 25"	94041015	17.5 R 25	TL	**	182 A2	CRC	L-5S	-	55.1	17.8	24.8	165.8	86	682	14.00/1.5	-
	94069941	17.5 R 25	TL	***	188 A2	CRC	L-5S	-	55.1	17.8	24.8	165.8	86	682	14.00/1.5	-
	94053629	18.00 R 25	TL	**	204 A2	CRC	L-5S	-	65.6	20.2	28.9	191.0	108	1235	13.00/2.5	-
	94515233	18.00 R 25	TL	***	206 A2	CRC	L-5S	-	65.6	20.2	28.9	191.0	108	1260	13.00/2.5	-
	94062348	20.5 R 25	TL	**	193 A2	CRC	L-5S	-	60.7	21.1	27.6	182.8	93	995	17.00/2.0	-
	94042128	26.5 R 25	TL	**	209 A2	CRC	L-5S	-	70.3	27.2	31.9	211.6	120	1762	22.00/3.0	-
	94075263	26.5 R 25	TL	***	214 A2	CRC	L-5S	-	70.3	27.2	31.9	211.6	120	1801	22.00/3.0	-
	94044160	29.5 R 25	TL	**	216 A2	CRC	L-5S	-	75.3	30.6	33.9	226.6	131	2249	25.00/3.5	-
Ø 29"	94040193	29.5 R 29	TL	**	218 A2	CRC	L-5S	-	79.1	30.5	35.9	238.1	131	2479	25.00/3.5	24.00/3.5 ; 26.00/3.5
	94515271	29.5 R 29	TL	***	223 A2	CRC	L-5S	-	79.1	30.5	35.9	238.1	131	2533	25.00/3.5	24.00/3.5 ; 26.00/3.5
Ø 33"	94061709	35/65 R 33	TL	**	224 A2	CRC	L-5S	-	81.3	35.4	36.0	243.1	125	2835	28.00/3.5	-

CRC: Cut Resistant Compound

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial

L-5S

A2

229

Technologies



Smooth Tire



Extra Deep Tread

Performance



Stability



Durability



Cut Resistance



	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 33"	94070350	35/65 R 33	TL	***	229 A2	CRC	L-5S	-	81.3	35.4	36.0	243.1	125	2904	28.00/3.5	-

CRC: Cut Resistant Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference