

# MP 567

|                     |                                      |
|---------------------|--------------------------------------|
| <b>TIRE SIZE</b>    | <b>18 - 19.5</b>                     |
| <b>UM</b>           | IS STANDARD                          |
| <b>CONSTRUCTION</b> | ⊗ BIAS                               |
| <b>MACHINERY</b>    | IMPLEMENT MACHINERY /<br>TELEHANDLER |
| <b>VERSION</b>      | STANDARD                             |
| <b>TIRE TYPE</b>    | TL                                   |
| <b>LI/SS</b>        | 160 B ; 162 A8                       |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 460  | <b>RIM REC</b> | 14.00           |
| <b>OD (MM)</b>  | 1104 | <b>ECE</b>     | E11-106R-003639 |
| <b>SLR (MM)</b> | 498  |                |                 |
| <b>RC (MM)</b>  | 3280 |                |                 |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>6.00</b> |
| 50                | 4500        |
| 40                | 4700        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.