



## EARTHMAX SR 44



### Description

EARTHMAX SR 44 (E-4) is an All Steel radial tire suitable transport applications with tippers. The rugged E-4 tread pattern provides both excellent traction and operator comfort. EARTHMAX SR 44 (E-4) ensures also great high load capacity and extraordinary durability.

### UM

IS Standard

### Construction

 Radial

### Machinery

OTR ■ On/Off Truck

Version	STANDARD
Tire Type	TT
Tyre size	325/95R24
LI/SS	158;B

## Dimensions IS Standard

OD (IS) (mm)	1250
SLR (IS) (mm)	575
RC (IS) (mm)	3790
Rim Rec	8.50V
Rim Alt	9.00V
TRA Code	E4

## Load Capacity (IS)

km/h / bar	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	3075	3150	3350	3450	3550	3650	3750	3875	4000	4125	4250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..