



PUDDLE SPECIAL (B)

Description

PUDDLE SPECIAL is a R-2 agricultural tire specifically designed for operations in paddy fields. The extra deep tread design along with the special lug pattern provides best grip and excellent traction even on wet and soft soil. The wide center bar provides better adaptability for road applications and provides extraordinary service performance. In addition, PUDDLE SPECIAL shows superior self-cleaning features and excellent durability.

UM

IS Standard

Construction

⊠ Bias

Machinery

Agriculture ■ Sprayer



Version

STANDARD

Tire Type

TL

Tyre size

120/90-26

LI/SS

90;A2

Dimensions IS Standard

SW (IS) (mm)	127
OD (IS) (mm)	940
SLR (IS) (mm)	448
RC (IS) (mm)	2847
Rim Rec	4 JA
ECE	E11-106R-005236

Load Capacity (IS)

km/h / bar	03:00:00																		
10	600																		

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..