



## FLOTATION TR 675



### Description

FLOTATION TR 675 is best suited for field and road transport. It fits trailers and implement machinery. FLOTATION TR 675 has been engineered to provide outstanding traction, high load capacity and a longer tire life.

### UM

IS Standard

### Construction

 Bias

### Machinery

Agriculture ■ Implement Machinery

Version	DUAL BEAD
Tire Type	TL
Tyre size	500/60-22.5
LI/SS	

## Dimensions IS Standard

SW (IS) (mm)	515
OD (IS) (mm)	1181
SLR (IS) (mm)	542
RC (IS) (mm)	3604
Rim Rec	AG 16.00
Rim Alt	15.00; 17.00
ECE	E11-106R-004395

## Load Capacity (IS)

km/h / bar	3.70	3.80	4.00
10 FR	7425	7545	7840
20 FR	6685	6790	7055
30 FR	5940	6035	6270
40 FR	5305	5390	5600
50 FR	4775	4850	5000
10 DW	5255	5340	5425
20 DW	4730	4805	4885
30 DW	4205	4275	4340
40 DW	3755	3815	3875
50 DW	3380	3435	3450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..