



## PUDDLE SPECIAL (B)



### Description

PUDDLE SPECIAL is a R-2 agricultural tire specifically designed for operations in paddy fields. The extra deep tread design along with the special lug pattern provides best grip and excellent traction even on wet and soft soil. The wide center bar provides better adaptability for road applications and provides extraordinary service performance. In addition, PUDDLE SPECIAL shows superior self-cleaning features and excellent durability.

### UM

IS Standard

### Construction

 Bias

### Machinery

Agriculture ■ Sprayer

Version	STANDARD
Tire Type	TT
Tyre size	120/90-26
LI/SS	90;A2

## Dimensions IS Standard

SW (IS) (mm)	127
OD (IS) (mm)	940
SLR (IS) (mm)	448
RC (IS) (mm)	2847
Rim Rec	4 JA
ECE	E11-106R-005236

## Load Capacity (IS)

km/h / bar	3.00
10	600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..