



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 30



PRODUCT DATA SHEET

EARTHMAX SR 30
RADIAL OTR TIRES



EARTHMAX SR 30 (E-3/L-3) is an *All Steel* radial tire which is dual-purposed for loaders and articulated dump trucks. The multi-layer steel belts and the rigid block pattern provide excellent traction, stability and durability. The special cut-resistant compound makes EARTHMAX SR 30 the ideal solution for a variety of harsh operating conditions.



Radial

E-3/L-3



208

Technologies



All Steel

Performance



Traction



Cut Resistance



Stability



Durability

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 25"	15.5 R 25	TL	E-3/L-3	**/*	160 B/169 A2	CRC	130	397	1276	574	3809	27	12.00/1.3	-
	17.5 R 25	TL	E-3/L-3	**/*	167 B/176 A2	CRC	150	446	1347	606	4021	29	14.00/1.5	-
	17.5 R 25	TL	L-3	***	188 A2	CRC	-	446	1347	606	4021	29	14.00/1.5	-
	20.5 R 25	TL	E-3/L-3	**/*	177 B/186 A2	CRC	170	529	1487	663	4439	32	17.00/2.0	17.00/1.7
	20.5 R 25	TL	L-3	**	193 A2	CRC	-	529	1487	663	4439	32	17.00/2.0	17.00/1.7
	23.5 R 25	TL	E-3/L-3	**/*	185 B/195 A2	CRC	200	612	1607	711	4797	34	19.50/2.5	-
	26.5 R 25	TL	E-3	**	193 B	CRC	230	689	1742	766	5200	38	22.00/3.0	-
	26.5 R 25	TL	E-3/L-3	**/*	193 B/202 A2	CRC	230	689	1742	766	5200	38	22.00/3.0	-
	26.5 R 25	TL	L-3	*	202 A2	CRC	-	689	1742	766	5200	38	22.00/3.0	-
	29.5 R 25	TL	E-3	**	200 B	CRC	270	765	1861	818	5555	42	25.00/3.5	-
	29.5 R 25	TL	E-3/L-3	**/*	200 B/208 A2	CRC	270	765	1861	818	5555	42	25.00/3.5	-
	29.5 R 25	TL	L-3	*	208 A2	CRC	-	765	1861	818	5555	42	25.00/3.5	-

CRC: Cut Resistant Compound

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference