



## RIDEMAX FL 693 M



### Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Tanker

Version	STANDARD
Tire Type	TL
Tyre size	VF400/45R17.5
LI/SS	159;D

## Dimensions IS Standard

SW (IS) (mm)	400
OD (IS) (mm)	800
SLR (IS) (mm)	343
RC (IS) (mm)	2357
Rim Rec	14.00
ECE	E11-106R-006068

## Load Capacity (IS)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
70	1000	1280	1595	1795	2075	2355	2595	2830	3110	3510	3985
65	1095	1400	1750	1970	2275	2585	2845	3110	3415	3850	4375
50	1325	1695	2120	2385	2755	3125	3445	3760	4135	4660	5295
40	1490	1905	2380	2680	3095	3515	3870	4225	4645	5240	5950
30	1655	2120	2645	2975	3440	3900	4300	4695	5160	5820	6610
25	1730	2215	2770	3115	3600	4080	4495	4910	5395	6090	6915
10	1970	2520	3150	3545	4095	4650	5120	5595	6145	6930	7875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..