



## ROCK SPECIAL (L-4)

### Description

ROCK SPECIAL (L-4) is a bias-ply tire engineered for loaders operating in severe mining and quarry applications. The extra deep rock pattern delivers excellent traction even under harsh operating conditions, while the wide footprint ensures great stability and operator comfort. ROCK SPECIAL (L-4) features a steel-belted heavy-duty casing and a particularly cut- and chip-resistant tread compound to provide excellent protection against external damage. The tire stands out for durability and reduced downtime, making it the ideal choice for the toughest requirements in rocky environments.



### UM

IS Standard

### Construction

### Machinery

OTR ■ Loader

|           |              |
|-----------|--------------|
| Version   | STEEL BELTED |
| Tire Type | TL           |
| Tyre size | 29.5-25      |
| LI/SS     |              |

# Dimensions IS Standard

|              |           |
|--------------|-----------|
| OD (IS) (mm) | 1880      |
| Rim Rec      | 25.00/3.5 |

## field\_1

|            |       |
|------------|-------|
| km/h / bar | 5.25  |
| 10         | 20000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..