



AGRIMAX PROHARVEST



AGRIMAX PROHARVEST is BKT's response to the current market needs in terms of combines and harvesting machines. The advanced VF (Very High Flexion) technology allows AGRIMAX PROHARVEST to carry 40% more load compared to standard tyres with the same tyre pressure minimizing soil compaction. Moreover, the three layers of steel belts combined with the cut and chip resistant compound ensure excellent puncture resistance, even on case of stubbles or crops leftovers on the field. The structure of the tyre with a reinforced bead and a strong polyester carcass is synonym of durability and stability of the tyre even during heavy duty operation.

US Standard

 Radial

Agriculture ■

STEEL BELTED

TL

VF900/60R32

193;D

undefined US Standard

94514403

34.7

74.8

33.0

224.9

DW 30 B

E11-106R-0010580

mph / psi	9	12	15	17	20	23	29	35	41	46
45	9010	10380	11770	13380	14770	16390	18230	18460	21460	23070
from 40 to 25	9890	11410	12930	14700	16230	18000	20030	20280	23580	25350
20	10090	11640	13190	15000	16560	18360	20440	20690	24050	25860
12	10280	11870	13450	15300	16880	18730	20830	21100	24530	26370
5	10880	12550	14230	16180	17860	19810	22030	22310	25940	27890
Upto 20 Cyc	11230	12950	14680	16700	18430	20440	22740	23030	26770	28780
Upto 10 Cyc	13400	15460	17530	19930	21990	24400	27150	27490	31950	34360
Upto 5 Cyc	14690	16950	19210	21850	24110	26740	29750	30120	35020	37650
10HT	10090	11640	13190	15000	16560	18360	20440	20690	24050	25860

25-02-2026