



SIERRA MAX



Description

SIERRA MAX is the BKT tire for both all-terrain and lawn and garden applications. Its radial construction provides a significantly smoother and more comfortable ride over extreme terrains such as deserts, or dirty and rocky surfaces. The special tread design along with its wider footprint provides outstanding forward and lateral traction.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ ATV

Version	STANDARD
Tire Type	TL
Tyre size	AT26x9R12
LI/SS	49;N

Dimensions IS Standard

SW (IS) (mm)	230
OD (IS) (mm)	660
SLR (IS) (mm)	304
RC (IS) (mm)	2009
Rim Rec	7.0
ECE	E11-75R-006225

Load Capacity (IS)

km/h / bar	0.50
140	185

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..