



US standard



GROWING TOGETHER

MP 600



PRODUCT DATA SHEET



Bias



MP 600

MP 600 is an agro-industrial tire, suitable for municipality/maintenance operations with telehandlers and implement machinery, providing a comfortable driving experience. This tire provides good traction and excellent self-cleaning properties along with an extended product life-cycle.

Performance



Comfort



Durability



Self-Cleaning



Traction

	US CODE	Tire size	Type	PR	LI/SS		Version	O.D.	S.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
					(In.)	(In.)		(In.)	(In.)	Rec.	Alt.				
Ø 18"	94015290	10.5 - 18	TL	10	-	-	STD	36.2	10.7	16.5	107.9	27	64	9	9 SDC
	94015306	12.5 - 18	TL	10	-	-	STD	39.0	12.1	17.7	116.1	30	97	11	12 SDC
	94015313	12.5 - 18	TL	12	-	-	STD	39.0	12.1	17.7	116.1	30	98	11	12 SDC
Ø 20"	94048403	400/70 - 20 (16.0/70 - 20)	TL	14	-	-	STD	42.7	15.9	-	-	42	153	13 SDC	12
Ø 24"	94042043	400/70 - 24 (16.0/70 - 24)	TL	10	-	-	STD	46.7	15.9	21.5	139.0	42	154	13 SDC	12
	94051618	400/70 - 24 (16.0/70 - 24)	TL	14	-	-	SPL	46.7	15.9	21.5	139.0	42	166	13 SDC	12
	94015320	400/70 - 24 (16.0/70 - 24)	TL	14	-	-	STD	46.7	15.9	21.5	139.0	42	171	13 SDC	12
	94049318	400/70 - 24 (16.0/70 - 24)	TL	18	158 A8	-	STD	46.7	15.9	21.5	139.0	42	169	13 SDC	12

STD: Standard - SPL: Special



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling