



## BK 826

### Description

BK 826 has been specially designed for trailers in haulage applications. It is a bias tire featuring high load capacity thanks to its reinforced carcass. BK 826 is also available as "industrial" version that shows particular cut and chip resistance and is also suitable for backhoe loaders.

### UM

US Standard

### Construction

 Bias

### Machinery

Agriculture ■ Trailer, ■ Trailer



Version	HARVESTER SPECIAL
Tire Type	TT
Tyre size	9.00-16
LI/SS	

## Dimensions US Standard

USA Code	94054879
SW (US) (in)	10.4
OD (US) (in)	36.4
Rim Rec	6.50 H
Rim Alt	6.00 G

## Load Capacity (US)

mph / psi	75
20	4190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..