



US standard



GROWING TOGETHER

# INDUSTRIAL RIB F3



PRODUCT DATA SHEET



Bias



Technologies



Special Compound

Performance



Durability



Stubble Resistance



# INDUSTRIAL RIB F3

INDUSTRIAL RIB F3 is an agro-industrial rib-pattern tire designed for field and road transport as well as for soil tillage operations with implement machinery and trailers. This tire features an outstanding stubble-resistant compound making it suitable for the most critical operating conditions and ensuring a long tire life-cycle.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 15"	94027521	11L - 15 SL	8 LB	10 LB	11.0	32.0	-	-	16	52	STD	12	TL	117A6
	94000111	11L - 15 SL	8 LB	10 LB	11.0	32.0	-	-	16	51	STD	10	TL	114A6
	94055494	11L - 15 SL	8 LB	10 LB	11.0	32.0	-	-	16	52	SR	10	TL	114A6
	94055500	11L - 15 SL	8 LB	10 LB	11.0	32.0	-	-	16	52	SR	12	TL	117A6
Ø 16"	94028689	11L - 16 SL	W 8 L	8 LB ; 10 LB ; W 10 L	11.0	32.7	-	-	16	53	SPL	10	TL	116A6
	94000173	11L - 16 SL	W 8 L	8 LB ; 10 LB ; W 10 L	11.0	32.7	-	-	16	54	STD	12	TL	120A6
	94000142	11L - 16 SL	W 8 L	8 LB ; 10 LB ; W 10 L	11.0	32.7	-	-	16	53	STD	10	TL	116A6

STD: Standard - SR: Stubble Resistant - SPL: Special



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference