



PRO RIB F2M



Description

PRO RIB F2M is an agricultural tire for 2WD tractors in soil tillage applications. It is particularly suitable for all operations requiring a high level of handling.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■ 2WD Tractor, Industrial & Construction ■ Trailer

Version	STANDARD
Tire Type	TT
Tyre size	11.00-16SL
LI/SS	114;A8

Dimensions IS Standard

SW (IS) (mm)	335
OD (IS) (mm)	950
SLR (IS) (mm)	440
RC (IS) (mm)	2830
Rim Rec	10 LB
Rim Alt	W 8 L; 8 LB
ECE	E4-106R-002667
TRA Code	F2M

Load Capacity (IS)

km/h / bar	2.80
40	1180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..