



FARM 2000

Description

The FARM 2000 tire is suitable on tractors for soil tillage and transport applications. It is the ideal tire for heavy-duty use and in all operating conditions where good traction is required.

UM

IS Standard

Construction

 Bias

Machinery

Agriculture ▪ Tractor



Version	SPECIAL
Tire Type	TT
Tyre size	12.4-28
LI/SS	125;A6

Dimensions IS Standard

SW (IS) (mm)	320
OD (IS) (mm)	1288
SLR (IS) (mm)	603
RC (IS) (mm)	3969
Rim Rec	W 11
Rim Alt	W 9; W 10
ECE	E11-106R-005965
TRA Code	R1

Load Capacity (IS)

km/h / bar	2.50
30	1650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..