



US standard



GROWING TOGETHER

LIFTMAX LM 63



PRODUCT DATA SHEET



Radial



LIFTMAX LM 63

LIFTMAX LM 63 has been specially developed for industrial and logistics operations. The *All-Steel* radial tire features a strong casing reinforced by multilayer steel belts that reduce vibration while providing enhanced stability and comfort. LIFTMAX LM 63 features a 3-rib tread design that ensures low rolling resistance as well as good wet grip and uniform tread wear, delivering improved handling performance. In addition, the deep tread extends the tire's service life.

Technologies



Performance



	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
							(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 8"	94067008	180/70 R 8 (18 X 7 R 8)	TL	-	125 A5	STD	18.1	6.7	-	-	16	23	4.33 R	-
	94067602	180/70 R 8 IMP (18 X 7 R 8)	TL	-	120 A8	STD	18.1	6.7	-	-	16	23	4.33 R	-
Ø 9"	94063901	6.00 R 9	TL	-	121 A5	STD	21.3	6.3	-	-	26	29	4.00 E	-
Ø 10"	94066247	6.50 R 10	TL	-	128 A5	STD	23.3	6.9	-	-	25	39	5.00 F	5.50 F
Ø 12"	94066209	7.00 R 12	TL	-	136 A5	STD	26.6	7.7	-	-	25	55	5.00 S	-
Ø 15"	94066834	7.00 R 15	TL	-	143 A5	STD	29.1	7.8	-	-	25	57	5.50	5.00
	94063635	8.25 R 15	TL	-	153 A5	STD	33.2	9.4	-	-	42	105	6.5	7.0
Ø 20"	94515387	12.00 R 20 NEWSIZE	TL	-	176 A5	STD	44.9	12.8	-	-	44	240	8.5	8.0

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference