



US standard



GROWING TOGETHER

FLOTATION TR 675



PRODUCT DATA SHEET



Bias



168

Performance



Durability



High Load Capacity



Traction



FLOTATION TR 675

FLOTATION TR 675 is best suited for field and road transport. It fits trailers and implement machinery. FLOTATION TR 675 has been engineered to provide outstanding traction, high load capacity and a longer tire life.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS	
			Rec.	Alt.										DW	FR
Ø 22.5"	94050147	500/60 - 22.5	AG 16.00	15.00; 17.00	20.3	46.5	21.3	141.9	47	231	DB	20	TL	155 A8/ 151 B	168 A8/ 164 B
	94019786	500/60 - 22.5	AG 16.00	15.00; 17.00	20.3	46.5	21.3	141.9	47	208	STD	12	TL	145 A8/ 142 B	157 A8/ 154 B
	94019793	500/60 - 22.5	AG 16.00	15.00; 17.00	20.3	46.5	21.3	141.9	47	209	STD	16	TL	151 A8/ 148 B	163 A8/ 159 B
	94047031	550/45 - 22.5	AG 16.00	-	21.4	42.1	-	-	47	194	STD	20	TL	154 A8/ 150 B	166 A8/ 162 B
	94019809	550/60 - 22.5	AG 16.00	-	21.7	49.6	21.5	143.3	47	236	STD	12	TL	148 A8/ 144 B	160 A8/ 156 B
	94019816	550/60 - 22.5	AG 16.00	-	21.7	49.6	21.5	143.3	47	251	STD	16	TL	154 A8/ 150 B	167 A8/ 163 B

DB: Dual Bead - STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling