



AT 316

Description

AT 316 is suitable for compact utility tractors in municipality and maintenance applications. The special tread design provides excellent traction without compromising field protection - an essential feature for this kind of application. AT 316 is also available as "aramid-belted" version to provide increased puncture resistance.

UM

US Standard

Construction

 Bias

Machinery

Agriculture ■ Compact Utility Tractor



Version ARAMID BELTED

Tire Type TL

Tyre size 24x12.00-12

LI/SS

Dimensions US Standard

| | |
|---------------|------------------------------|
| USA Code | 94001217 |
| SW (US) (in) | 12.4 |
| OD (US) (in) | 24.0 |
| SLR (US) (in) | 10.7 |
| RC (US) (in) | 69.6 |
| Rim Rec | 10.50 - 55; - 70; - 90 |

Load Capacity (US)

| | |
|-----------|------|
| mph / psi | 32 |
| 10 | 2270 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..