



EARTHMAX SR LOADER

Description

EARTHMAX SR LOADER is an OTR tire specifically designed for loading and dozing operations. Its All Steel casing along with multi-layer steel belts and a unique tread compound provide exceptional resistance to snags and punctures resulting in an extended service life. EARTHMAX SR LOADER features a unique tread pattern providing top selfcleaning properties and excellent traction on several types of terrain.

UM

US Standard

Construction

 Radial

Machinery

OTR ■ Rigid Dump Truck



Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	20.5R25undefined
LI/SS	177;177

Dimensions US Standard

USA Code	94064250
OD (US) (in)	58.1
SLR (US) (in)	25.6
RC (US) (in)	172.6
Rim Rec	17.00/2.0
TRA Code	E3/L3

Load Capacity (US)

mph / psi	58	62	65	69	73	76
30	12800	13600	14300	14800	15200	16100
5	17600	18200	19300	19800	20900	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..