



FLOTATION 648



Description

FLOTATION 648 is particularly suitable for field and road transport as well as for spreading operations. Some sizes are designed for hay harvesters/balers. The special tread design allows for carrying very heavy loads at low pressure, guaranteeing at the same time reduced soil compaction and preventing damage to crops.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■ Baler

Version

STANDARD

Tire Type

TL

Tyre size

400/60-22.5

LI/SS

Dimensions IS Standard

SW (IS) (mm)	400
OD (IS) (mm)	1070
SLR (IS) (mm)	475
RC (IS) (mm)	3233
Rim Rec	AG 11.75
ECE	E11-106R-004389

Load Capacity (IS)

km/h / bar	05:30:00	06:00:00	06:30:00																
10 FR	7170	7400	7630																
20 FR	6450	6660	6865																
30 FR	5735	5920	6105																
40 FR	5120	5285	5450																
50 FR	4610	4755	4875																
10 DW	5095	5265	5425																
20 DW	4585	4740	4885																
30 DW	4075	4210	4340																
40 DW	3640	3760	3875																
50 DW	3275	3385	3450																

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by

industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..