



LIFTMAX LM 63

Description

LIFTMAX LM 63 has been specially developed for industrial and logistics operations. The All-Steel radial tire features a strong casing reinforced by multilayer steel belts that reduce vibration while providing enhanced stability and comfort. LIFTMAX LM 63 features a 3-rib tread design that ensures low rolling resistance as well as good wet grip and uniform tread wear, delivering improved handling performance. In addition, the deep tread extends the tire's service life.



UM

IS Standard

Construction

 Radial

Machinery

Industrial & Construction ■ Tow Tractor

Version	STANDARD
Tire Type	TL
Tyre size	180/70R8IMP
LI/SS	120;A8

Dimensions IS Standard

OD (IS) (mm)	460
Rim Rec	4.33R
ECE	E11-106R-006845

Load Capacity (IS)

km/h / bar	10.00
40	1400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..