



## EARTHMAX SR 315

### Description

SR 315 is an all steel (UMS) radial tire specially engineered and designed for LHD. It delivers excellent performance in dig and load and carry operations in underground mines. Strong casing reinforced by multiple steel belts minimizes impact break and rock punctures. Reinforced sidewalls minimize rock cuts and damage caused by scrubbing. Specially formulated underground mine service (UMS) compound for low heat generation, reliability, protection against rock cuts and damage.



### UM

IS Standard

### Construction

 Radial

### Machinery

OTR ■ Load Haul Dump

Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	26.5R29
LI/SS	217;A2

## Dimensions IS Standard

OD (IS) (mm)	1865
SLR (IS) (mm)	830
RC (IS) (mm)	5635
Rim Rec	22.00/3.0
TRA Code	L35

## Load Capacity (IS)

km/h / bar	6.75	7.00	7.25	7.50	7.75	8.00
10	20000	20600	21200	21800	22400	23000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..