



AGRIMAXFACTOR

Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors perfect for haulage and soil tillage operations. The improved tread design with increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance. AGRIMAXFACTOR's overall advantages are great handling in combination with driving comfort and excellent durability. The exclusive sidewall shows the "E-READY" logo that highlights BKT's commitment to electric mobility.



UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor

Version	STANDARD
Tire Type	TL
Tyre size	420/70R28
LI/SS	133;D

Dimensions IS Standard

SW (IS) (mm)	418
OD (IS) (mm)	1349
SLR (IS) (mm)	606
RC (IS) (mm)	4000
Rim Rec	W 13
Rim Alt	W 12; W 14 L
ECE	E11-106R-007652
TRA Code	R1W

Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	1135	1320	1505	1690	1875	2060
50	1195	1390	1585	1780	1975	2165
40	1245	1450	1650	1855	2060	2260
30	1305	1520	1735	1945	2160	2370
10 LT	1525	1770	2020	2270	2520	2765
10 HT	1305	1520	1735	1945	2160	2370

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..