



MULTIMAX MP 569

Description

MULTIMAX MP 569 is a high-performance radial tire engineered for demanding industrial applications. MULTIMAX MP 569 is the ideal choice for equipping telehandlers and other construction equipment such as industrial tractors and excavators. The deep tread design, combined with wide shoulder lugs, ensures exceptional traction and flotation on multiple surfaces. The tire's All-Steel radial construction provides exceptional durability and superior resistance to punctures, significantly extending service life.



UM

IS Standard

Construction

 Radial

Machinery

Industrial & Construction ■ Telehandler

Version	STANDARD
Tire Type	TL
Tyre size	445/65R22.5
LI/SS	169;J

Dimensions IS Standard

OD (IS) (mm)	1174
SLR (IS) (mm)	528
RC (IS) (mm)	3558
Rim Rec	13.00
Rim Alt	14.00
ECE	E11-54R-0019094

Load Capacity (IS)

km/h / bar	9.00
100	5800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..