



IS standard



GROWING TOGETHER

FARM SPECIAL



PRODUCT DATA SHEET



Bias



A6



Technologies



Reinforced Carcass

Performance



Self-Cleaning



Traction



High Load Capacity



Cut and Chip Resistance



Durability



FARM SPECIAL

FARM SPECIAL is a tractor tire suitable for soil tillage operations. The strong casing provides a high level of puncture resistance and a longer service life, whilst the rounded shoulders prevent soil damages ensuring the protection of the valuable crops. FARM SPECIAL features a unique tread design with special mud breakers for best self-cleaning properties. In addition, dual angled lugs provide excellent traction and reduced slippage.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 24"	9.5 - 24	W 8	W 7	240	1050	491	3194	STD	8	TT	112 A6
	11.2 - 24	W 10	W 9	285	1095	509	3283	STD	8	TT	116 A6
	12.4 - 24	W 11	W 9; W 10	320	1155	534	3504	STD	8	TT	121 A6
	13.6 - 24	W 12	W 11	350	1205	554	3635	STD	8	TT	123 A6
Ø 28"	14.9 - 24	W 13	W 11; W 12	378	1255	572	3775	STD	8	TT	128 A6
	11.2 - 28	W 10	W 9	285	1205	563	3694	STD	8	TT	118 A6
	12.4 - 28	W 11	W 9; W 10	315	1265	589	3853	STD	8	TT	123 A6
	13.6 - 28	W 12	W 11	350	1310	610	3985	STD	8	TT	125 A6
Ø 30"	14.9 - 28	W 13	W 11; W 12	375	1355	620	4105	STD	8	TT	130 A6
	16.9 - 30	W 15 L	W 14 L	431	1469	671	4456	STD	8	TT	137 A6
Ø 32"	18.4 - 30	W 16 L	W 15 L	451	1533	689	4599	STD	8	TT	139 A6
	12.4 - 32	W 11	W 9; W 10	320	1360	634	4137	STD	8	TT	124 A6
Ø 36"	13.6 - 36	W 12	W 11	345	1515	704	4591	STD	8	TT	129 A6
Ø 38"	13.6 - 38 (14.00 - 38)	W 12	W 11	345	1565	736	4874	STD	8	TT	131 A6
	14.00 - 38 (13.6 - 38)	W 12	W 11	345	1565	736	4874	STD	8	TT	131 A6
	15.5 - 38	W 14 L	-	394	1575	731	4813	STD	8	TT	133 A6

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference