



RIDEMAX FL 693 M



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings.

UM

US Standard

Construction

Machinery

Agriculture ■ Tanker

Version	HD
Tire Type	TL
Tyre size	650/55R26.5
LI/SS	178;D

Dimensions US Standard

USA Code	94049622
SW (US) (in)	25.4
OD (US) (in)	54.7
SLR (US) (in)	24.2
RC (US) (in)	167.3
Rim Rec	AG 20.00
ECE	E11-106R-003008

field_2

mph / psi	15	17	23	29	35	41	46	52	58	73
40	5130	6120	7440	8600	9920	11240	12070	13390	14720	15540
30	6210	7410	9010	10410	12000	13610	14600	16210	17810	18820
25	6980	8320	10120	11690	13490	15300	16420	18220	20020	21140
20	7750	9250	11240	12980	14980	16990	18230	20230	22220	23480
15	8100	9670	11760	13590	15670	17770	19080	21160	23260	24560
5	9230	11010	13390	15480	17860	20240	21730	24110	26490	27980

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..