



SM 55 L5S

Description

SM 55 (L-5S) is a bias-ply tire ideal for underground mining operations. The specially designed cut-and-chip-resistant tread compound minimizes punctures thereby reducing machine downtime. The extra-deep L-5 S tread depth guarantees an extended tire life. The tire is also available in a steel-belted version.

UM

IS Standard

Construction

◆ Bias

Machinery

OTR ■ Underground Mining Vehicle



Version	STEEL BELTED
Tire Type	TL
Tyre size	17.5-25
LI/SS	

Dimensions IS Standard

OD (IS) (mm)	1375
SLR (IS) (mm)	631
RC (IS) (mm)	4043
Rim Rec	14.00/1.5
Rim Alt	14.00/1.3; 14.00/1.4 (DC)
TRA Code	L5S

Load Capacity (IS)

km/h / bar	5.75
10	8250
15	7180
25	6600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..