



FLOTATION 351



Description

FLOTATION 351 is a bias flotation tire which best suits transport applications using trailers. Extra deep lugs provide outstanding traction and a longer tire life. FLOTATION 351 is the ideal tire on wet and moist surfaces ensuring high load capacity.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■ Trailer

Version	STANDARD
Tire Type	TL
Tyre size	66x43.00-25
LI/SS	160;B

Dimensions IS Standard

SW (IS) (mm)	1020
OD (IS) (mm)	1750
SLR (IS) (mm)	782
RC (IS) (mm)	5213
Rim Rec	36.0 TH
ECE	E11-106R-004378
TRA Code	HF3

Load Capacity (IS)

km/h / bar	1.70
50	4500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..