



## EARTHMAX SR 484



### Description

EARTHMAX SR 484 is an All Steel truck tire for transport in surface mines. It offers excellent protection in harsh and rocky conditions, with excellent self-cleaning properties. The steel belts allow for superior performance in drilling, enhancing uptime and increasing productivity.

### UM

IS Standard

### Construction

Radial

### Machinery

OTR ■ Rigid Dump Truck

Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	27.00R49
LI/SS	223;B

## Dimensions IS Standard

OD (IS) (mm)	2647
SLR (IS) (mm)	1193
RC (IS) (mm)	8055
Rim Rec	19.50/4.0
TRA Code	E3

## Load Capacity (IS)

km/h / bar	05:00:00	05:25:00	05:50:00	06:15:00	06:00:00	06:25:00	06:50:00	07:15:00	07:00:00
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or omissions in the contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by applicable laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in any form or format or otherwise without prior written consent by Balkrishna Industries Ltd..