



AGRIMAX V-FLECTO

Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.



UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ High-Power Tractor

Version	STANDARD
Tire Type	TL
Tyre size	VF340/85R28
LI/SS	139;D

Dimensions IS Standard

SW (IS) (mm)	355
OD (IS) (mm)	1290
SLR (IS) (mm)	571
RC (IS) (mm)	3833
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-0010342

Load Capacity (IS)

km/h / bar	0.6	0.8	1	1.2	1.4	1.6
70	1215	1410	1610	1810	2010	2210
from 65 to 40	1335	1555	1770	1990	2210	2430
30	1360	1580	1805	2025	2250	2475
20	1385	1615	1840	2070	2295	2525
10	1600	2135	2670	3200	2425	2670
*Upto 10 Cyc with front loader	1870	2175	2480	2785	3090	3400
10HT	1360	1580	1805	2025	2250	2475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..