



RIDEMAX IT 696



Description

RIDEMAX IT 696 has a unique tread design and a wide footprint that provides excellent grip for road applications, even in winter conditions. The tire is best suitable for transport and municipality/maintenance applications thanks to its high-speed feature and strong casing. The tread design has been specifically developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor

Version	STANDARD
Tire Type	TL
Tyre size	540/80R38IND
LI/SS	172;A8

Dimensions IS Standard

SW (IS) (mm)	550
OD (IS) (mm)	1829
SLR (IS) (mm)	833
RC (IS) (mm)	5537
Rim Rec	W 18 L
Rim Alt	W 16 L
ECE	E11-106R-004077

Load Capacity (IS)

km/h / bar	0.6	0.8	1	1.2	1.4	1.6
65	1075	1250	1425	1600	1775	1950
50	1130	1315	1500	1685	1870	2050
40	1180	1370	1565	1755	1950	2140
30	1235	1440	1640	1845	2045	2245
10 LT	1440	1675	1910	2145	2380	2615
10HT	1235	1440	1640	1845	2045	2245

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..