



AGRIMAX V-FLECTO

Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ High-Power Tractor



Version

SPECIAL

Tire Type

TL

Tyre size

650/85R42

LI/SS

183;D

Dimensions IS Standard

SW (IS) (mm)	680
OD (IS) (mm)	2160
SLR (IS) (mm)	938
RC (IS) (mm)	6413
Rim Rec	DW 23 B
Rim Alt	DW20B;DW21B
ECE	E11-106R-0011307
TRA Code	R1W

Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	3980	4615	5250	5970	6605	7240	7960
from 65 to 40	4375	5075	5775	6560	7260	7960	8750
30	4460	5175	5890	6690	7405	8120	8925
20	4550	5275	6005	6825	7550	8280	9100
10	4810	5580	6350	7215	7985	8755	9625
Upto 30 Cyc	4965	5755	6550	7445	8240	9035	9930
Upto 15 Cyc	5925	6875	7820	8890	9835	10785	11855
Upto 10 Cyc	6495	7530	8570	9740	10780	11820	12990
10HT	4460	5175	5890	6690	7405	8120	8925

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..