



MULTIMAX MP 522



Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ▪ Compact Loader, Industrial & Construction ▪ Compact Loader

| | |
|-----------|--------------|
| Version | STANDARD |
| Tire Type | TL |
| Tyre size | 280/80R18IND |
| LI/SS | 132;A8/B |

Dimensions US Standard

| | |
|---------------|-----------------|
| USA Code | 94045044 |
| SW (US) (in) | 11.1 |
| OD (US) (in) | 35.7 |
| SLR (US) (in) | 16.6 |
| RC (US) (in) | 108.2 |
| Rim Rec | W 9; 9; 9 SDC |
| Rim Alt | W 8; W 10 |
| ECE | E11-106R-002962 |

Load Capacity (US)

| mph / psi | 23 | 29 | 35 | 41 | 46 | 51 | 58 | 61 | 64 |
|-----------|------|------|------|------|------|------|------|------|-------|
| 30 | 2120 | 2510 | 2870 | 3260 | 3660 | 3920 | 4410 | - | - |
| 25 | 2120 | 2510 | 2870 | 3260 | 3660 | 3920 | 4410 | - | - |
| 20 | 2270 | 2690 | 3080 | 3490 | 3920 | 4200 | 4720 | - | - |
| 15 | 2360 | 2800 | 3190 | 3630 | 4070 | 4360 | 4890 | - | - |
| 5 Cyc. | 2580 | 3170 | 3740 | 4300 | 4890 | 5320 | 6020 | 6350 | 6610 |
| Static | 3960 | 4870 | 5730 | 6590 | 7510 | 8170 | 9240 | 9740 | 10140 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..