



## BK 208

### Description

BK 208 is suitable for transport applications on trailers and light trucks. It is a considerably durable and reliable tire for both in-the-field and on-the-road usage.

### UM

US Standard

### Construction

 Bias

### Machinery

Agriculture ▪ Compact Utility Tractor



Version	STANDARD
Tire Type	TT
Tyre size	7.50-16
LI/SS	

## Dimensions US Standard

USA Code	94013234
SW (US) (in)	8.3
OD (US) (in)	31.9
Rim Rec	6.00 G

## Load Capacity (US)

mph / psi	-
-	-
-	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..