



TRAC MASTER



Description

TRAC MASTER is a soil tillage and lawn and garden tire, suitable for small tractors and implement machinery. Its tread design provides excellent field protection along with great traction in the fields and optimum self-cleaning properties.

UM

IS Standard

Construction

 Bias

Machinery

Agriculture ▪ Implement Machinery

Version	STANDARD
Tire Type	TL
Tyre size	31x15.50-15
LI/SS	

Dimensions IS Standard

SW (IS) (mm)	405
OD (IS) (mm)	792
SLR (IS) (mm)	370
RC (IS) (mm)	2372
Rim Rec	13 LB
ECE	E4-106R-002208

Load Capacity (IS)

km/h / bar	3.10
50	1250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..