



## PORTMAX PM 90



### Description

PORTMAX PM 90 has been specially designed for reach stackers in several applications including industrial handling and steelworks. It is an All Steel radial tire that provides great durability and stability. Its special antistatic tread compound ensures particular heat resistance and an extended tire life-cycle. PORTMAX PM 90 offers reduced rolling resistance improving fuel economy.

### UM

US Standard

### Construction

 Radial

### Machinery

Industrial & Construction ■ Reach Stacker

Version	INDUSTRIAL
Tire Type	TL
Tyre size	18.00R25
LI/SS	207;A5

## Dimensions US Standard

USA Code	94045662
OD (US) (in)	65.2
SLR (US) (in)	28.7
RC (US) (in)	197.8
Rim Rec	13.00/2.5

## Load Capacity (US)

mph / psi	145
15	38600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..