



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 45 H2




PRODUCT DATA SHEET



Radial



Technologies



All Steel



Block Pattern

Performance



Durability



Traction



Stability



High Load Capacity



EARTHMAX SR 45 H2

RADIAL OTR TIRES

EARTHMAX SR 45 H2 is an All Steel radial tire specifically designed for rigid haul trucks. The E-4 tread depth and the unique tread pattern ensure excellent wear minimizing vibration and noise. EARTHMAX SR 45 H2 is ideal for all operations requiring traction and stability. The All Steel casing provides excellent resistance to snags and punctures and a long service life. Available in standard, heat-resistant and cut-resistant compounds.

Ø 35"	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
24.00 R 35	TL	E-4	**	209 B	STDC	390	660	2180	978	6597	70	17.00/3.5	-	
24.00 R 35	TL	E-4	**	209 B	CRC	333	660	2180	978	6597	70	17.00/3.5	-	
24.00 R 35	TL	E-4	**	209 B	HRC	435	660	2180	978	6597	70	17.00/3.5	-	
24.00 R 35	TL	E-4	***	212 B	STDC	390	660	2180	978	6597	70	17.00/3.5	-	
24.00 R 35	TL	E-4	***	212 B	CRC	333	660	2180	978	6597	70	17.00/3.5	-	
24.00 R 35	TL	E-4	***	212 B	HRC	435	660	2180	978	6597	70	17.00/3.5	-	

CRC: Cut Resistance Compound - HRC: Heat Resistant Compound - STDC: Standard Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference