



MINE STAR

Description

MINE STAR is a bias-ply tire which is an excellent choice for heavy-duty underground mining operations. It features high cut/chip and puncture resistance providing improved operational efficiency. MINE STAR is made of a special compound and features a special tread design resulting in an extended tire life-cycle.

UM

US Standard

Construction

 Bias

Machinery

OTR ■ Underground Mining Vehicle



Version	STANDARD
Tire Type	TL
Tyre size	55x19.00-34
LI/SS	

Dimensions US Standard

USA Code	94069897
SW (US) (in)	18.1
OD (US) (in)	56.5
Rim Rec	16.00
TRA Code	L5

Load Capacity (US)

mph / psi	145
3	38100
5	33800
10	31400
15	28700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..